

HIGH-VOLUME TIRE CHANGERS

monty[®]
TIRE CHANGING SYSTEMS

3550



HOFMANN[®] 

3550



INNOVATIVE TIRE CHANGER FOR HIGH-VOLUME SHOPS

Hofmann's monty® 3550 series of high-performance tire changers feature the industry's most advanced capabilities to service a wide variety of wheel and tire assemblies. The monty 3550 series is specifically designed to change low-profile, high performance and run-flat tires maximizing a shop's versatility.

ACCOMMODATES LARGE WHEEL & TIRE ASSEMBLIES

- Allowing for a tire diameter of 47" and an outer-wheel diameter of 26" on the monty 3550 can handle wheel and tire assemblies found on cars and light trucks

DUAL WHEEL CLAMPING CYLINDERS

- Dual pneumatic clamping cylinders control all four clamping jaws, eliminating damage to wheel due to slippage

FOUR-JAW CLAMPING CHUCK

- Self-centering and clamps wheels with either 28" inner or 26" outer diameter

POWERFUL TWO-POSITION BEAD BREAKER

- 6,000 lbs of power at the bead shovel and a range of up to 17" wide. The two-stage pneumatic cylinder provides precise power and can be toggled with the foot pedal as needed

PNEUMATICALLY-CONTROLLED MOUNT/DEMOUNT HEAD

- Push-button controlled mount/demount head pneumatically lowers and locks into position, automatically indexing away from the wheel to prevent contact and damage to the wheel and tire assembly

PROTECT THE MOST DELICATE WHEELS

- All metal parts have plastic protection providing non-metal to metal contact when changing delicate wheels

PATENTED SMARTSPEED™ TECHNOLOGY (EEWH747B)

- Automatically minimizes damage to tires
- Innovative, patented technology that optimizes the torque applied to the wheel and automatically sets the maximum rotation speed of the wheel
- Variable from 7 RPM to 18 RPM offering the highest possible speed for maximum productivity

TECHNICAL SPECIFICATIONS

Inner wheel clamping diameter	12" - 28" (30.5 - 71 cm)
Outer wheel clamping diameter	12" - 26" (30.5 - 66 cm)
Single speed power requirements	115V 1Ph 60Hz
smartSpeed power requirements	230V 1Ph 60Hz
Air pressure required	110-170 psi

STANDARD ACCESSORIES

EasyMont Pro bead assist device	Quick change bead head
Snap-in jaw protector	Protective cover for tire lever
Protective cover for bead breaker shovel	Rim protector
Replacement composite head	Wave tire tool
Magic Bead pusher	Bead clamp for performance wheels
Premium tire paste	

OPTIONAL ACCESSORIES

Motorcycle/ATV adapters	EAA0329G53A
-------------------------	-------------

For more information regarding the monty® 3550,
call 800.251.4500 (US) or 501.505.2662 (Canada)
www.hofmann-usa.com / www.hofmann.ca

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet piece may change without notice. ©2016 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.
08/21 SS2734G

